

Injection system FIS EB with anchor rod FIS A resp. RG M

Permissible loads of a single anchor¹⁾²⁾ in normal concrete of strength class C20/25.
For the design the complete current assessment ETA-15/0440 has to be considered.

| Type | Material / surface ³⁾ | Effective anchorage depth h_{ef} [mm] | Minimum member thickness h_{min} [mm] | Maximum installation torque $T_{Inst,max}$ [Nm] | Cracked concrete | | | | Non-cracked concrete | | | |
|------------|----------------------------------|---|---|---|--|-------------------------|------------------------|------------------------|--|-------------------------|------------------------|------------------------|
| | | | | | Permissible tension (N_{perm}) and shear loads (V_{perm}); minimum spacing (s_{min}) and edge distances (c_{min}) with reduced loads | | | | Permissible tension (N_{perm}) and shear loads (V_{perm}); minimum spacing (s_{min}) and edge distances (c_{min}) with reduced loads | | | |
| | | | | | $N_{perm}^{4)}$ [kN] | $V_{perm}^{4)}$ [kN] | $s_{min}^{4)}$ [mm] | $c_{min}^{4)}$ [mm] | $N_{perm}^{4)}$ [kN] | $V_{perm}^{4)}$ [kN] | $s_{min}^{4)}$ [mm] | $c_{min}^{4)}$ [mm] |
| FIS A M 8 | 5.8 | 60 | 100 | 10 | 3.6 | 5.1 | 40 | 40 | 7.9 | 5.1 | 40 | 40 |
| | 5.8 | 80 | 110 | 10 | 4.8 | 5.1 | 40 | 40 | 9.0 | 5.1 | 40 | 40 |
| | 5.8 | 160 | 190 | 10 | 9.0 | 5.1 | 40 | 40 | 9.0 | 5.1 | 40 | 40 |
| | R-70 | 60 | 100 | 10 | 3.6 | 6.0 | 40 | 40 | 7.9 | 6.0 | 40 | 40 |
| | R-70 | 80 | 110 | 10 | 4.8 | 6.0 | 40 | 40 | 9.9 | 6.0 | 40 | 40 |
| | R-70 | 160 | 190 | 10 | 9.6 | 6.0 | 40 | 40 | 9.9 | 6.0 | 40 | 40 |
| FIS A M 10 | 5.8 | 60 | 100 | 20 | 4.5 | 8.6 | 45 | 45 | 9.0 | 8.6 | 45 | 45 |
| | 5.8 | 90 | 120 | 20 | 6.7 | 8.6 | 45 | 45 | 13.5 | 8.6 | 45 | 45 |
| | 5.8 | 200 | 230 | 20 | 13.8 | 8.6 | 45 | 45 | 13.8 | 8.6 | 45 | 45 |
| | R-70 | 60 | 100 | 20 | 4.5 | 9.0 | 45 | 45 | 9.0 | 9.2 | 45 | 45 |
| | R-70 | 90 | 120 | 20 | 6.7 | 9.2 | 45 | 45 | 13.5 | 9.2 | 45 | 45 |
| | R-70 | 200 | 230 | 20 | 15.0 | 9.2 | 45 | 45 | 15.7 | 9.2 | 45 | 45 |
| FIS A M 12 | 5.8 | 70 | 100 | 40 | 6.3 | 12.0 | 55 | 55 | 12.6 | 12.0 | 55 | 55 |
| | 5.8 | 110 | 140 | 40 | 9.9 | 12.0 | 55 | 55 | 19.7 | 12.0 | 55 | 55 |
| | 5.8 | 240 | 270 | 40 | 20.5 | 12.0 | 55 | 55 | 20.5 | 12.0 | 55 | 55 |
| | R-70 | 70 | 100 | 40 | 6.3 | 12.6 | 55 | 55 | 12.6 | 13.7 | 55 | 55 |
| | R-70 | 110 | 140 | 40 | 9.9 | 13.7 | 55 | 55 | 19.7 | 13.7 | 55 | 55 |
| | R-70 | 240 | 270 | 40 | 21.5 | 13.7 | 55 | 55 | 22.5 | 13.7 | 55 | 55 |
| FIS A M 16 | 5.8 | 80 | 120 | 60 | 7.7 | 15.3 | 65 | 65 | 16.8 | 22.3 | 65 | 65 |
| | 5.8 | 125 | 170 | 60 | 12.0 | 22.3 | 65 | 65 | 27.0 | 22.3 | 65 | 65 |
| | 5.8 | 320 | 360 | 60 | 30.6 | 22.3 | 65 | 65 | 37.6 | 22.3 | 65 | 65 |
| | R-70 | 80 | 120 | 60 | 7.7 | 15.3 | 65 | 65 | 16.8 | 25.2 | 65 | 65 |
| | R-70 | 125 | 170 | 60 | 12.0 | 23.9 | 65 | 65 | 26.9 | 25.2 | 65 | 65 |
| | R-70 | 320 | 360 | 60 | 30.6 | 25.2 | 65 | 65 | 42.0 | 25.2 | 65 | 65 |
| FIS A M 20 | 5.8 | 90 | 140 | 120 | 10.8 | 21.5 | 85 | 85 | 20.0 | 34.9 | 85 | 85 |
| | 5.8 | 170 | 220 | 120 | 20.3 | 34.9 | 85 | 85 | 40.7 | 34.9 | 85 | 85 |
| | 5.8 | 400 | 450 | 120 | 47.9 | 34.9 | 85 | 85 | 58.6 | 34.9 | 85 | 85 |
| | R-70 | 90 | 140 | 120 | 10.8 | 21.5 | 85 | 85 | 20.0 | 39.4 | 85 | 85 |
| | R-70 | 170 | 220 | 120 | 20.3 | 39.4 | 85 | 85 | 40.7 | 39.4 | 85 | 85 |
| | R-70 | 400 | 450 | 120 | 47.9 | 39.4 | 85 | 85 | 65.7 | 39.4 | 85 | 85 |
| FIS A M 24 | 5.8 | 96 | 160 | 150 | 12.9 | 30.8 | 105 | 105 | 18.4 | 44.1 | 105 | 105 |
| | 5.8 | 210 | 270 | 150 | 31.4 | 50.9 | 105 | 105 | 50.3 | 50.9 | 105 | 105 |
| | 5.8 | 480 | 540 | 150 | 71.8 | 50.9 | 105 | 105 | 84.3 | 50.9 | 105 | 105 |
| | R-70 | 96 | 160 | 150 | 12.9 | 30.8 | 105 | 105 | 18.4 | 44.1 | 105 | 105 |
| | R-70 | 210 | 270 | 150 | 31.4 | 56.8 | 105 | 105 | 50.3 | 56.8 | 105 | 105 |
| | R-70 | 480 | 540 | 150 | 71.8 | 56.8 | 105 | 105 | 94.3 | 56.8 | 105 | 105 |
| FIS A M 30 | 5.8 | 120 | 190 | 300 | 18.0 | 43.1 | 140 | 140 | 25.7 | 61.6 | 140 | 140 |
| | 5.8 | 280 | 350 | 300 | 52.4 | 80.6 | 140 | 140 | 78.5 | 80.6 | 140 | 140 |
| | 5.8 | 600 | 670 | 300 | 112.2 | 80.6 | 140 | 140 | 133.8 | 80.6 | 140 | 140 |
| | R-70 | 120 | 190 | 300 | 18.0 | 43.1 | 140 | 140 | 25.7 | 61.6 | 140 | 140 |
| | R-70 | 280 | 350 | 300 | 52.4 | 90.2 | 140 | 140 | 78.5 | 90.2 | 140 | 140 |
| | R-70 | 600 | 670 | 300 | 112.2 | 90.2 | 140 | 140 | 150.1 | 90.2 | 140 | 140 |

¹⁾ Design according to EN 1992-4:2018 (for static resp. quasi-static loads). The partial safety factors for material resistance as regulated in the ETA as well as a partial safety factor for load actions of $\gamma_L = 1.4$ are considered. As a single anchor counts e.g. an anchor with a spacing $s \geq 3 \times h_{gr}$ and an edge distance $c \geq 1.5 \times h_{gr}$. Accurate data see ETA.

²⁾ The specified loads are valid for anchorages in dry and damp concrete. For temperatures in the anchoring substrate up to 50 °C (resp. short term up to 80 °C). Drill hole cleaning as per specification in the ETA. The factor Ψ_{sus} for sustained load was taken into account with 1.0.

³⁾ Further steel grades, versions and technical data see ETA, e.g. for dry internal conditions, galvanised steel (gvz); for damp interiors and for outdoor use, stainless steel (R).

⁴⁾ In the case of combinations of tension and shear loads, bending moments with reduced or minimum spacing and edge distances (anchor groups), the design must be carried out in accordance with the provisions of the complete ETA and the provisions of the EN 1992-4:2018. We recommend using our anchor design software C-FIX.